

μCOM-43 SINGLE CHIP MICROCOMPUTER
DESCRIPTION

The μPD553 is a high negative output version of the μCOM-43. This PMOS, -10 volt part is designed with outputs capable of being pulled to -35 volts. This allows direct interfacing with Fluorescent Indicator Panels (FIPs). As a μCOM-43, it includes 2000 x 8 ROM, 96 x 4 RAM and 35 I/O lines in a 42 pin plastic dual-in-line package.

ABSOLUTE MAXIMUM RATING*

Operating Temperature	-10°C to +70°C
Storage Temperature	-40°C to +125°C
Supply Voltage	-15 to +0.3 Volts
Input Voltages (Port A, INT, RES, TEST)	-15 to +0.3 Volts
(All Other Inputs)	-40 to +0.3 Volts
Output Voltages	-40 to +0.3 Volts
Output Current (Each Output Bit)	-12 mA
(Total Current)	-60 mA

COMMENT: Stress above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

* $T_a = 25^\circ\text{C}$

DC/AC CHARACTERISTICS

$T_a = -10^\circ\text{C} \text{ to } +70^\circ\text{C}$, $V_{GG} = -10V \pm 10\%$


PARAMETER	SYMBOL	LIMITS			UNIT	TEST CONDITIONS
		MIN	TYP	MAX		
Input High Voltage	V_{IH}	0		-3.5	V	Ports A to D, INT, RES
Input Low Voltage	V_{IL1}	-7.5		V_{GG}	V	Ports A and B, INT, RES
	V_{IL2}	-7.5		-35	V	Ports C and D
Input Leakage Current High	I_{LH}			+10	μA	Ports A and B, INT, RES, TEST $V_I = -1V$
Input Leakage Current Low	I_{LIL1}			-10	μA	Ports A and B, INT, RES, TEST $V_I = -11V$
	I_{LIL2}			-30	μA	Ports A and B $V_I = -35V$
I/O Leakage Current High	I_{IOH}			+10	μA	Ports C and D $V_I = -1V$
I/O Leakage Current Low	I_{IOL1}			-10	μA	Ports C and D $V_I = -11V$
	I_{IOL2}			-30	μA	Ports C and D $V_I = -35V$
Output Voltage	V_{OH}			-2.0	V	Ports C to I $I_O = -8 \text{ mA}$
Output Leakage Current	I_{OL1}			-10	μA	Ports C to I $V_O = -11V$
	I_{OL2}			-30	μA	Ports C to I $V_O = -35V$
Supply Current	I_{GG}		-30	-50	mA	
Oscillator Frequency	F	150		440	KHz	

μ PD553


T_a = 25°C, f = 1 MHz

CAPACITANCE

PARAMETER	SYMBOL	LIMITS			UNIT	TEST CONDITIONS
		MIN	TYP	MAX		
Input Capacitance	C _I			15	pf	f = 1 MHz
Output Capacitance	C _O			15	pf	
Input/Output Capacitance	C _{IO}			15	pf	



CLOCK WAVEFORM



PACKAGE OUTLINE
 μ PD553C

ITEM	MILLIMETERS	INCHES
A	56.0 MAX	2.2 MAX
B	2.6 MAX	0.1 MAX
C	2.54	0.1
D	0.5 ± 0.1	0.02 ± 0.004
E	50.8	2.0
F	1.5	0.059
G	3.2 MIN	0.126 MIN
H	0.5 MIN	0.02 MIN
I	5.22 MAX	0.20 MAX
J	5.72 MAX	0.22 MAX
K	15.24	0.6
L	13.2	0.52
M	0.3 ± 0.1	0.01 ± 0.004