



AMD

PROCESSOR

RECOGNITION

Application Note

Publication # 20734	Rev: D Amendment/0
Issue Date: January 1997	

This document contains information on a product under development at Advanced Micro Devices (AMD). The information is intended to help you evaluate this product. AMD reserves the right to change or discontinue work on this proposed product without notice.

© 1997 Advanced Micro Devices, Inc. All rights reserved.

Advanced Micro Devices, Inc. ("AMD") reserves the right to make changes in its products without notice in order to improve design or performance characteristics.

The information in this publication is believed to be accurate at the time of publication, but AMD makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication or the information contained herein, and reserves the right to make changes at any time, without notice. AMD disclaims responsibility for any consequences resulting from the use of the information included in this publication.

This publication neither states nor implies any representations or warranties of any kind, including but not limited to, any implied warranty of merchantability or fitness for a particular purpose. AMD products are not authorized for use as critical components in life support devices or systems without AMD's written approval. AMD assumes no liability whatsoever for claims associated with the sale or use (including the use of engineering samples) of AMD products except as provided in AMD's Terms and Conditions of Sale for such product.

Trademarks

AMD, the AMD logo, and combinations thereof are trademarks of Advanced Micro Devices, Inc.

Am486 is a registered trademark, and K86, Am5x86, AMD-K5, AMD-K6, and the AMD-K6 logo are trademarks of Advanced Micro Devices, Inc.

Other product names used in this publication are for identification purposes only and may be trademarks of their respective companies.

Contents

List of Figures	iv
List of Tables	iv
Introduction	1
Using the CPUID Instruction	2
Overview	2
Testing for the CPUID Instruction	2
Using CPUID Functions	3
Identifying the Processor's Vendor	4
Testing For Extended Functions	5
Determining the Processor Signature	5
Identifying Supported Features	6
AMD Processor Signature	8
Displaying the Processor's Name	9
Displaying Cache Information	9
Sample Code	10
Appendix A	11
CPUID	11
Standard Functions	12
Extended Functions	14
Appendix B	18

List of Figures

Figure 1.	Contents of EAX Register Returned by Function 1	5
Figure 2.	Contents of EAX Register Returned by Extended Function 8000_0001h	9

List of Tables

Table 1.	Summary of CPUID Functions in AMD Processors	4
Table 2.	Summary of Processor Signatures for AMD Processors	6
Table 3.	Summary of Standard Feature Bits for AMD Processors	7
Table 4.	Summary of Extended Feature Bits for AMD Processors	8
Table 5.	Standard Feature Flag Descriptions	13
Table 6.	Extended Feature Flag Descriptions	15
Table 7.	EBX Format Returned by Function 8000_0005h	17
Table 8.	ECX Format Returned by Function 8000_0005h	17
Table 9.	EDX Format Returned by Function 8000_0005h	17
Table 10.	Values Returned By AMD Processors	18

AMD Processor Recognition

Introduction

Due to the increasing number of choices available in the x86 processor marketplace, the need for a simple way for hardware and software to identify the type of processor and its feature set has become critical. The CUID instruction was added to the x86 instruction set for this purpose.

The CUID instruction provides complete information about the processor (vendor, type, name, etc.) and its capabilities (features). After detecting the processor and its capabilities, software can be accurately tuned to the system for maximum performance and benefit to users. For example, game software can test the performance level available from a particular processor by detecting the type or speed of the processor. If the performance level is high enough, the software can enable additional capabilities or more advanced algorithms. Another example involves testing for the presence of multimedia extensions (MMX) on the processor. If the software finds this feature present when it checks the feature bits, it can utilize these more powerful extensions for dramatically better performance on new multimedia software.

Using the CUID Instruction

Overview

Software operating at any privilege level can execute the CUID instruction to identify the processor and its feature set. In addition, the CUID instruction implements multiple functions, each providing different information about the processor, including the vendor, model number, revision (stepping), features, cache organization, and processor name. The multiple-function approach allows the CUID instruction to return a complete picture about the type of processor and its capabilities—more detailed information than could be returned by a single function. In addition to gathering all the information by calling multiple functions, the CUID instruction provides the flexibility of making only one call to obtain the specific data requested once the processor vendor has been identified.

The functions are divided into two types: standard functions and extended functions. Standard functions provide a simple way for software to access information common to all x86 processors. Extended functions provide information on extensions specific to a vendor's processors (e.g., AMD's processors).

The flexibility of the CUID instruction allows for the addition of new CUID functions in future generations of processors. Appendix A on page 11 contains a detailed description of the CUID instruction.

Testing for the CUID Instruction

Beginning with the Am486®DX4 processor, all AMD processors implement the CUID instruction. In order to avoid an invalid opcode exception on those processors that do not support the CUID instruction, software must first test to determine if the CUID instruction is present on the processor. The presence of the CUID instruction is indicated by the ID bit (21) in the EFLAGS register. If this bit is writeable, the CUID instruction is implemented on the processor.

Software uses the PUSHFD and POPFD instructions to write to the ID bit in the EFLAGS register. After reading the ID bit, a comparison determines if this operation changed the value of the ID bit. If the value changed, the CPUID instruction is available for identifying the processor and its features. The following code sample demonstrates the way a program uses the PUSHFD and POPFD instructions to test the ID bit.

```
pushfd                ; Save EFLAGS to stack
pop    eax            ; Store EFLAGS in EAX
mov    ebx, eax       ; Save in EBX for testing later
xor    eax, 00200000h ; Switch bit 21
push   eax            ; Copy "changed" value to stack
popfd                ; Save "changed" EAX to EFLAGS
pushfd                ; Push EFLAGS to top of stack
pop    eax            ; Store EFLAGS in EAX
cmp    eax, ebx       ; See if bit 21 has changed
jz     NO_CPUID       ; If no change, no CPUID
```

Using CPUID Functions

When software uses the CPUID instruction to identify a processor, it is important that it uses the instruction appropriately. The instruction has been defined to make it easy to identify the type and features of x86 processors manufactured by many different vendors.

The standard functions (EAX=0 and EAX=1) are the same for all processors. Having standard functions simplifies software's task of testing for and implementing features common to x86 processors. Software can test for these features and, as new x86 processors are released, benefit from these capabilities immediately.

Extended functions are specific to a vendor's processors. These functions provide additional information about AMD processors that software can use to identify enhanced features and functions. To test for extended functions, software checks for "AuthenticAMD" in the vendor identification string returned by function 0 and for a non-zero value in the EAX register returned by function 8000_0000h.

Within AMD's family of processors, different members can execute a different number of functions. Table 1 summarizes the CPUID functions currently implemented on AMD processors.

Table 1. Summary of CPUID Functions in AMD Processors
(Appendix A contains detailed descriptions of the functions.)

Standard Function	Extended Function	Description	Am486DX4 and Am5x86™ Processors	AMD-K5™ Processor (model 0)	AMD-K5 Processor (model 1, 2, & 3)	AMD-K6™ MMX Processor (model 6)
0	—	Vendor String and Largest Standard Function Value	X	X	X	X
1	—	Processor Signature and Standard Feature Bits	X	X	X	X
—	8000_0000h	Largest Extended Function Value	—	—	X	X
—	8000_0001h	Extended Processor Signature and Extended Feature Bits	—	—	X	X
—	8000_0002h	Processor Name	—	—	X	X
—	8000_0003h	Processor Name	—	—	X	X
—	8000_0004h	Processor Name	—	—	X	X
—	8000_0005h	Cache Information	—	—	X	X
Note: <i>Future versions of these processors may implement additional functions.</i>						

Identifying the Processor's Vendor

Software must execute the standard function EAX=0. The CPUID instruction returns a 12-character string that identifies the processor's vendor. The instruction also returns the largest standard function input value defined for the CPUID instruction on the processor.

For AMD processors, function 0 returns a vendor string of "AuthenticAMD". This string informs the software to follow AMD's definition for subsequent CPUID functions and the registers returned for those functions.

Once the software identifies the processor's vendor, it knows the definition for all the functions supplied by the CPUID instruction. By using these functions, the software obtains the processor information needed to properly tune its functionality to the capabilities of the processor.

Testing For Extended Functions

Once software has identified the processor’s vendor as AMD, it must test for extended functions by executing function 8000_0000h. The EAX register returns the largest extended function input value defined for the CPUTID instruction on the processor. If this value is non-zero, extended functions are supported.

To simplify identifying processors and their features, the AMD extended functions include all the information provided in the standard functions as well as the additional AMD-specific feature enhancements. This duplication can minimize the number of function calls required by software.

Determining the Processor Signature

Standard function 1 (EAX=1) of the CPUTID instruction returns the standard processor signature and feature bits. The standard processor signature is returned in the EAX register and provides information regarding the specific revision (stepping) and model of the processor and the instruction family level supported by the processor. The revision level is used to determine if the processor requires the implementation of software workarounds. Figure 1 shows the contents of the EAX register obtained by function 1. Table 2 summarizes the specific processor signature values returned for AMD processors.




Figure 1. Contents of EAX Register Returned by Function 1

Table 2. Summary of Processor Signatures for AMD Processors
(Appendix A contains details on bit locations and values.)

Processor	Instruction Family	Model	Stepping ID
Am486 and Am5x86 Processors	0100b (4h)	yyyy ²	xxx ¹
AMD-K5 Processor (Model 0)	0101b (5h)	0000b (0h)	xxx ¹
AMD-K5 Processor (Model 1)	0101b (5h)	0001b (1h)	xxx ¹
AMD-K5 Processor (Model 2)	0101b (5h)	0010b (2h)	xxx ¹
AMD-K5 Processor (Model 3)	0101b (5h)	0011b (3h)	xxx ¹
AMD-K6 MMX Processor	0101b (5h)	0110b (6h)	xxx ¹
Notes: <ol style="list-style-type: none"> 1. Contact your AMD representative for the latest stepping information. 2. Model identifier information is provided in the AMD BIOS Development Guide, order# 19720. 			

Identifying Supported Features

The feature bits are returned in the EDX register for two CPUID functions: standard function 1 and extended function 8000_0001h. Each bit corresponds to a specific feature and indicates if that feature is present on the processor. Table 3 summarizes the standard feature bits, and Table 4 summarizes the extended feature bits.

Before using any of the enhanced features added to the latest generation of processors, software should test each feature bit returned by functions 1 and 8000_0001h to identify the capabilities available on the processor. For example, software must test bit 23 to determine if the processor has MultiMedia eXtensions (MMX). Attempting to execute an unavailable feature can cause errors and exceptions.

Table 3. Summary of Standard Feature Bits for AMD Processors
(Appendix A contains details on bit locations and values.)

Feature	Description
Floating-Point Unit	A floating-point unit is available.
Virtual Mode Extensions	Virtual mode extensions are available.
Debugging Extensions	I/O breakpoint debug extensions are supported.
Page Size Extensions	4-Mbyte pages are supported.
Time Stamp Counter (with RDTSC and CR4 disable bit)	A time stamp counter is available in the processor, and the RDTSC instruction is supported.
K86™ Model-Specific Registers (with RDMSR and WRMSR)	The K86 model-specific registers are available in the processor, and the RDMSR and WRMSR instructions are supported.
Machine Check Exception	The machine check exception is supported.
CMPXCHG8B Instruction	The CMPXCHG8B instruction is supported.
APIC	A local APIC unit is available.
Global Paging Extension	Global paging extensions are available.
Conditional Move Instruction	The conditional move instructions CMOV, FCMOV, and FCOMI are supported.
MultiMedia eXtensions	The MultiMedia eXtensions (MMX) are supported.

Table 4. Summary of Extended Feature Bits for AMD Processors
(Appendix A contains details on bit locations and values.)

Feature	Description
Floating-Point Unit	A floating-point unit is available.
Virtual Mode Extensions	Virtual mode extensions are available.
Debugging Extensions	I/O breakpoint debug extensions are supported.
Page Size Extensions	4-Mbyte pages are supported.
Time Stamp Counter (with RDTSC and CR4 disable bit)	A time stamp counter is available in the processor, and the RDTSC instruction is supported.
K86 Model-Specific Registers (with RDMSR and WRMSR)	The K86 model-specific registers are available in the processor, and the RDMSR and WRMSR instructions are supported.
Machine Check Exception	The machine check exception is supported.
CMPXCHG8B Instruction	The CMPXCHG8B instruction is supported.
Global Paging Extension	Global paging extensions are available.
SYSCALL and SYSRET Extensions	The SYSCALL and SYSRET instructions and associated extensions are supported.
Integer Conditional Move Instruction	The integer conditional move instruction CMOV is supported.
Floating-Point Conditional Move Instructions	The floating-point conditional move instructions FCMOV and FCOMI are supported.
MultiMedia eXtensions	The MultiMedia eXtensions (MMX) are supported.

AMD Processor Signature

Extended function 8000_0001h returns the AMD processor signature. The signature is returned in the EAX register and provides generation, model, and stepping information for AMD processors. Figure 2 shows the contents returned in the EAX register. See Table 2 for a summary of the values returned by specific AMD processors.




Figure 2. Contents of EAX Register Returned by Extended Function 8000_0001h

Displaying the Processor's Name

Functions 8000_0002h, 8000_0003h, and 8000_0004h return an ASCII string containing the name of the processor. These functions eliminate the need for software to search for the processor name in a lookup table, a process requiring a large block of memory and frequent updates. Instead, software can simply call these three functions to obtain the name string (48 ASCII characters in little endian format) and display it on the screen. Although the name string can be up to 48 characters in length, shorter names have the remaining byte locations filled with the ASCII NULL character (00h). To simplify the display routines and avoid using screen space, software only needs to display characters until a NULL character is detected.

Displaying Cache Information

Function 8000_0005h provides cache information for the processor. Some diagnostic software displays information about the system and the processor's configuration. It is common for this type of software to provide cache size and organization of information. Function 8000_0005h provides a simple way for software to obtain information about the on-chip cache and TLB structures. The size and organization information is returned in the registers as described in Appendix A on page 11. Software can simply display these values, eliminating the need for large pieces of code to test the memory structures.

Sample Code

A code sample that uses the CPUID instruction to identify the processor and its features is available from AMD's website at <http://www.amd.com>.

Appendix A

CPUID

<i>mnemonic</i>	<i>opcode</i>	<i>description</i>
CPUID	0F A2h	Identify the processor and its feature set
Privilege:	none	
Registers Affected:	EAX, EBX, ECX, EDX	
Flags Affected:	none	
Exceptions Generated:	none	

The CPUID instruction is an application-level instruction that software executes to identify the processor and its feature set. This instruction offers multiple functions, each providing a different set of information about the processor. The CPUID instruction can be executed from any privilege level. Software can use the information returned by this instruction to tune its functionality for the specific processor and its features.

Not all processors implement the CPUID instruction. Therefore, software must test to determine if the instruction is present on the processor. If the ID bit (21) in the EFLAGS register is writeable, the CPUID instruction is implemented.

The CPUID instruction supports multiple functions. The information associated with each function is obtained by executing the CPUID instruction with the function number in the EAX register. Functions are divided into two types: standard functions and extended functions. Standard functions are found in the low function space, 0000_0000h–7FFF_FFFFh. In general, all x86 processors have the same standard function definitions.

Extended functions are defined specifically for processors supplied by the vendor listed in the vendor identification string. Extended functions are found in the high function space, 8000_0000h–8FFF_FFFFh. Because not all vendors have defined extended functions, software must test for their presence on the processor.

AMD processors have extended functions under the following conditions:

- The processor returns the “AuthenticAMD” vendor identification string.
- The 8000_0000h function returns a non-zero value in the EAX register.

Standard Functions

Function 0 – Largest Standard Function Input Value and Vendor Identification String

Input: EAX = 0

Output: EAX = Largest function input value recognized by the CPUID instruction
EBX, EDX, ECX = Vendor identification string

This is a standard function found in all processors implementing the CPUID instruction. It returns two values. The first value is returned in the EAX register and indicates the largest standard function value recognized by the processor. The second value is the vendor identification string. This 12-character ASCII string is returned in the EBX, EDX, and ECX registers in little endian format.

AMD processors return a vendor identification string of “AuthenticAMD” that software uses as follows:

- To identify the processor as an AMD processor
- To apply AMD’s definition of the CPUID instruction for all additional function calls

Function 1 – Processor Signature and Standard Feature Flags

Input: EAX = 1

Output: EAX = Processor Signature
EBX = Reserved
ECX = Reserved
EDX = Standard Feature Flags

Function 1 returns two values—the Processor Signature and the Standard Feature Flags. The processor signature is returned in the EAX register and identifies the specific processor by providing information on its type—instruction family, model, and revision (stepping). The information is formatted as follows:

- EAX[3–0] Stepping ID
- EAX[7–4] Model
- EAX[11–8] Instruction Family
- EAX[31–2] Reserved

The standard feature flags are returned in the EDX register and indicate the presence of specific features. In most cases, a “1” indicates the feature is present, and a “0” indicates the feature is not present. Table 5 contains a list of the currently defined standard feature flags. Reserved bits will be used for new features as they are added.

Table 5. Standard Feature Flag Descriptions

Bit	Feature	Description
0	Floating-Point Unit	0 = No FPU 1 = FPU Present
1	Virtual Mode Extensions	0 = No Support 1 = Support
2	Debugging Extensions	0 = No Support 1 = Support
3	Page Size Extensions	0 = No Support 1 = Support 4Mbyte Pages
4	Time Stamp Counter (with RDTSC and CR4 disable bit)	0 = No Support 1 = Support
5	K86 Model-Specific Registers (with RDMSR and WRMSR)	0 = No Support 1 = Support
6	Reserved	—
7	Machine Check Exception	0 = No Support 1 = Support
8	CMPXCHG8B Instruction	0 = No Support 1 = Support
9	APIC*	0 = No Support 1 = Support
10–11	Reserved	—
12	Memory Type Range Registers	0 = No Support 1 = Support
13	Global Paging Extension*	0 = No Support 1 = Support
14	Reserved	—
15	Conditional Move Instruction	0 = No Support 1 = Support
16–22	Reserved	—
23	MultiMedia eXtensions (MMX)	0 = No Support 1 = Support
24–31	Reserved	—

Note:

* The AMD-K5 processor (model 0) reserves bit 13 and implements feature bit 9 to indicate support for Global Paging Extensions instead of support for APIC.

Extended Functions

Function 8000_0000h – Largest Extended Function Input Value

Input: EAX = 8000_0000h

Output: EAX = Largest function input value recognized by the CPUID instruction
EBX = Reserved
ECX = Reserved
EDX = Reserved

Function 8000_0000h returns a value in the EAX register that indicates the largest extended function value recognized by the processor.

Function 8000_0001h – AMD Processor Signature and Extended Feature Flags

Input: EAX = 8000_0001h

Output: EAX = AMD Processor Signature
EBX = Reserved
ECX = Reserved
EDX = Extended Feature Flags

Function 8000_0001h returns two values—the AMD Processor Signature and the Extended Feature Flags. The AMD processor signature is returned in the EAX register and identifies the specific processor by providing information regarding its type—generation/family, model, and revision (stepping). The information is formatted as follows:

- EAX[3–0] Stepping ID
- EAX[7–4] Model
- EAX[11–8] Generation/Family
- EAX[31–12] Reserved

The extended feature flags are returned in the EDX register and indicate the presence of specific features found in AMD processors. In most cases, a “1” indicates the feature is present, and a “0” indicates the feature is not present. Table 6 contains a list of the currently defined feature flags. Reserved bits will be used for new features as they are added.

Table 6. Extended Feature Flag Descriptions

Bit	Feature	Description
0	Floating-Point Unit	0 = No FPU 1 = FPU Present
1	Virtual Mode Extensions	0 = No Support 1 = Support
2	Debugging Extensions	0 = No Support 1 = Support
3	Page Size Extensions	0 = No Support 1 = Support 4Mbyte Pages
4	Time Stamp Counter (with RDTSC and CR4 disable bit)	0 = No Support 1 = Support
5	K86 Model-Specific Registers (with RDMSR and WRMSR)	0 = No Support 1 = Support
6	Reserved	—
7	Machine Check Exception	0 = No Support 1 = Support
8	CMPXCHG8B Instruction	0 = No Support 1 = Support
9	Reserved	—
10	SYSCALL and SYSRET Extensions	0 = No Support 1 = Support
11–12	Reserved	—
13	Global Paging Extension	0 = No Support 1 = Support
14	Reserved	—
15	Integer Conditional Move Instructions	0 = No Support 1 = Support
16	Floating-Point Conditional Move Instructions	0 = No Support 1 = Support
17–22	Reserved	—
23	MultiMedia eXtensions (MMX)	0 = No Support 1 = Support
24–31	Reserved	—

Functions 8000_0002h, 8000_0003h, and 8000_0004h – Processor Name String

Input: EAX = 8000_0002h, 8000_0003h, or 8000_0004h

Output: EAX = Processor Name String
EBX = Processor Name String
ECX = Processor Name String
EDX = Processor Name String

Functions 8000_0002h, 8000_0003h, and 8000_0004h return the processor name string in the EAX, EBX, ECX, and EDX registers. These three functions use the four registers to return an ASCII string of up to 48 characters in little endian format. The NULL character (ASCII 00h) is used to indicate the end of the processor name string. This feature is useful for processor names that require fewer than 48 characters.

Function 8000_0005h – Cache Information

Input: EAX = 8000_0005h

Output: EAX = Reserved
EBX = TLB Information
ECX = L1 Data Cache Information
EDX = L1 Instruction Cache Information

Function 8000_0005h returns information about the processor's on-chip caches. Tables 7, 8, and 9 provide the format for the information returned by the 8000_0005h function.

Table 7. EBX Format Returned by Function 8000_0005h

	Data TLB		Instruction TLB	
	Associativity*	# Entries	Associativity*	# Entries
EBX	Bits 31–24	Bits 23–16	Bits 15–8	Bits 7–0
Note: * Full associativity is indicated by a value of 0FFh.				

Table 8. ECX Format Returned by Function 8000_0005h

	L1 Data Cache			
	Size (Kbytes)	Associativity*	Lines per Tag	Line Size (bytes)
ECX	Bits 31–24	Bits 23–16	Bits 15–8	Bits 7–0
Note: * Full associativity is indicated by a value of 0FFh.				

Table 9. EDX Format Returned by Function 8000_0005h

	L1 Instruction Cache			
	Size (Kbytes)	Associativity*	Lines per Tag	Line Size (bytes)
EDX	Bits 31–24	Bits 23–16	Bits 15–8	Bits 7–0
Note: * Full associativity is indicated by a value of 0FFh.				

Appendix B

Table 10 contains all the values returned for AMD processors by the CUID instruction.

Table 10. Values Returned By AMD Processors

Function Register	Am486 and Am5x86 Processors	AMD-K5 Processor (Model 0)	AMD-K5 Processor (Model 1)	AMD-K5 Processor (Model 2)	AMD-K5 Processor (Model 3)	AMD-K6 MMX Processor (Model 6)
Function: 0						
EAX	0000_0001h	0000_0001h	0000_0001h	0000_0001h	0000_0001h	0000_0001h
EBX	6874_7541h	6874_7541h	6874_7541h	6874_7541h	6874_7541h	6874_7541h
ECX	444D_4163h	444D_4163h	444D_4163h	444D_4163h	444D_4163h	444D_4163h
EDX	6974_6E65h	6974_6E65h	6974_6E65h	6974_6E65h	6974_6E65h	6974_6E65h
Function: 1						
EAX	0000_04XXh	0000_050Xh	0000_051Xh	0000_052Xh	0000_053Xh	0000_056Xh
EBX	Reserved	Reserved	Reserved	Reserved	Reserved	Reserved
ECX	Reserved	Reserved	Reserved	Reserved	Reserved	Reserved
EDX	0000_0001h	0000_03BFh	0000_21BFh	0000_21BFh	0000_21BFh	0080_01BFh
Function: 8000_0000h						
EAX	0000_0000h	0000_0000h	8000_0005h	8000_0005h	8000_0005h	8000_0005h
EBX	Undefined	Undefined	Reserved	Reserved	Reserved	Reserved
ECX	Undefined	Undefined	Reserved	Reserved	Reserved	Reserved
EDX	Undefined	Undefined	Reserved	Reserved	Reserved	Reserved
Function: 8000_0001h						
EAX	Undefined	Undefined	0000_051Xh	0000_052Xh	0000_053Xh	0000_066Xh
EBX	Undefined	Undefined	Reserved	Reserved	Reserved	Reserved
ECX	Undefined	Undefined	Reserved	Reserved	Reserved	Reserved
EDX	Undefined	Undefined	0000_21BFh	0000_21BFh	0000_21BFh	0080_05BFh
Function: 8000_0002h						
EAX	Undefined	Undefined	2D44_4D41h	2D44_4D41h	2D44_4D41h	2D44_4D41h
EBX	Undefined	Undefined	7428_354Bh	7428_354Bh	7428_354Bh	6D74_364Bh
ECX	Undefined	Undefined	5020_296Dh	5020_296Dh	5020_296Dh	202F_7720h
EDX	Undefined	Undefined	6563_6F72h	6563_6F72h	6563_6F72h	746C_756Dh

Table 10. Values Returned By AMD Processors (continued)

Function Register	Am486 and Am5x86 Processors	AMD-K5 Processor (Model 0)	AMD-K5 Processor (Model 1)	AMD-K5 Processor (Model 2)	AMD-K5 Processor (Model 3)	AMD-K6 MMX Processor (Model 6)
Function: 8000_0003h EAX EBX ECX EDX	Undefined Undefined Undefined Undefined	Undefined Undefined Undefined Undefined	726F_7373h 0000_0000h 0000_0000h 0000_0000h	726F_7373h 0000_0000h 0000_0000h 0000_0000h	726F_7373h 0000_0000h 0000_0000h 0000_0000h	6465_6D69h 6520_6169h 6E65_7478h 6E6F_6973h
Function: 8000_0004h EAX EBX ECX EDX	Undefined Undefined Undefined Undefined	Undefined Undefined Undefined Undefined	0000_0000h 0000_0000h 0000_0000h 0000_0000h	0000_0000h 0000_0000h 0000_0000h 0000_0000h	0000_0000h 0000_0000h 0000_0000h 0000_0000h	0000_0073h 0000_0000h 0000_0000h 0000_0000h
Function: 8000_0005h EAX EBX ECX EDX	Undefined Undefined Undefined Undefined	Undefined Undefined Undefined Undefined	Reserved 0480_0000h 0804_0120h 1004_0120h	Reserved 0480_0000h 0804_0120h 1004_0120h	Reserved 0480_0000h 0804_0120h 1004_0120h	Reserved 0280_0140h 2002_0220h 2002_0220h

Sales Offices

North American

ALABAMA	(205) 830-9192
ARIZONA	(602) 242-4400
CALIFORNIA,	
Calabasas	(818) 878-9988
Irvine	(714) 450-7500
Sacramento (Roseville)	(916) 786-6700
San Diego	(619) 560-7030
San Jose	(408) 922-0300
CANADA, Ontario,	
Kanata	(613) 592-0060
Woodbridge	(905) 856-3377
COLORADO	(303) 741-2900
CONNECTICUT	(203) 264-7800
FLORIDA,	
Clearwater	(813) 530-9971
Ft. Lauderdale	(954) 938-9550
Orlando (Longwood)	(407) 862-9292
GEORGIA	(770) 449-7920
IDAHO	(208) 377-0393
ILLINOIS, Chicago (Itasca)	(708) 773-4422
KENTUCKY	(606) 224-1353
MARYLAND	(410) 381-3790
MASSACHUSETTS	(617) 273-3970
MINNESOTA	(612) 938-0001
NEW JERSEY,	
Cherry Hill	(609) 662-2900
Parsippany	(201) 299-0002
NEW YORK,	
Brewster	(914) 279-8323
Rochester	(716) 425-8050
NORTH CAROLINA,	
Charlotte	(704) 875-3091
Raleigh	(919) 878-8111
OHIO,	
Columbus (Westerville)	(614) 891-6455
Dayton	(513) 439-0268
OREGON	(503) 245-0080
PENNSYLVANIA	(610) 398-8006
TEXAS,	
Austin	(512) 346-7830
Dallas	(214) 934-9099
Houston	(713) 376-8084

International

AUSTRALIA, N Sydney	TEL	(61) 2 9959-1937
.....	FAX	(61) 2 9959-1037
BELGIUM, Antwerpen	TEL	(03) 248-4300
.....	FAX	(03) 248-4642
CHINA,		
Beijing	TEL	(8610) 501-1566
.....	FAX	(8610) 465-1291
Shanghai	TEL	(8621) 6267-8857
.....	TEL	(8621) 6267-9883
.....	FAX	(8621) 6267-8110
FINLAND, Helsinki	TEL	(358) 9 881 3117
.....	FAX	(358) 9 804 1110
FRANCE, Paris	TEL	(1) 49-75-1010
.....	FAX	(1) 49-75-1013
GERMANY,		
Bad Homburg	TEL	(06172) 92670
.....	FAX	(06172) 23195
München	TEL	(089) 450530
.....	FAX	(089) 406490
HONG KONG, Kowloon	TEL	(852) 2956-0388
.....	FAX	(852) 2956-0588
ITALY, Milano	TEL	(02) 381961
.....	FAX	(02) 3810-3458
JAPAN,		
Osaka	TEL	(06) 243-3250
.....	FAX	(06) 243-3253
Tokyo	TEL	(03) 3346-7600
.....	FAX	(03) 3346-5197

KOREA, Seoul	TEL	(82) 2784-0030
.....	FAX	(82) 2784-8014
SINGAPORE, Singapore	TEL	(65) 337-7033
.....	FAX	(65) 338-1611
SCOTLAND, Stirling	TEL	(44) 7186-450024
.....	FAX	(44) 1786-446188
SWITZERLAND, Geneva	TEL	(41) 22-788-0251
.....	FAX	(41) 22-788-0617
SWEDEN,		
Stockholm area	TEL	(08) 629-2850
(Bromma)	FAX	(08) 98-0906
TAIWAN, Taipei	TEL	(886) 2715-3536
.....	FAX	(886) 2712-2182
UNITED KINGDOM,		
London area	TEL	(01483) 74-0440
(Woking)	FAX	(01483) 75-6196
Manchester area	TEL	(01925) 83-0380
(Warrington)	FAX	(01925) 83-0204

North American Representatives

ARIZONA,		
Scottsdale – THORSON DESERT STATES	(602) 998-2444	
CALIFORNIA,		
Chula Vista – SONIKA ELECTRONICA	(619) 498-8340	
CANADA,		
Burnaby, B.C. – DAVETEK MARKETING	(604) 430-3680	
Dorval, Quebec – POLAR COMPONENTS	(514) 683-3141	
Kanata, Ontario – POLAR COMPONENTS	(613) 592-8807	
Woodbridge, Ontario – POLAR COMPONENTS	(416) 410-3377	
ILLINOIS,		
Skokie – INDUSTRIAL REPS, INC.	(847) 967-8430	
INDIANA,		
Kokomo – SCHILLINGER ASSOC.	(317) 457-7241	
IOWA,		
Cedar Rapids – LORENZ SALES	(319) 377-4666	
KANSAS,		
Merriam – LORENZ SALES	(913) 469-1312	
Wichita – LORENZ SALES	(316) 721-0500	
MEXICO,		
Guadalajara – SONIKA ELECTRONICA	(523) 647-4250	
Mexico City – SONIKA ELECTRONICA	(525) 754-6480	
Monterrey – SONIKA ELECTRONICA	(528) 358-9280	
MICHIGAN,		
Brighton – COM-TEK SALES, INC	(810) 227-0007	
Holland – COM-TEK SALES, INC	(616) 335-8418	
MINNESOTA,		
Edina – MEL FOSTER TECH. SALES, INC	(612) 941-9790	
MISSOURI,		
St Louis – LORENZ SALES	(314) 997-4558	
NEBRASKA,		
Lincoln – LORENZ SALES	(402) 475-4660	
NEW YORK,		
Plainview – COMPONENT CONSULTANTS	(516) 273-5050	
East Syracuse – NYCOM	(315) 437-8343	
Fairport – NYCOM	(716) 425-5120	
OHIO,		
Centerville – DOLFUSS ROOT & CO	(513) 433-6776	
Powell – DOLFUSS ROOT & CO	(614) 781-0725	
Middleburg Hts – DOLFUSS ROOT & CO	(216) 816-1660	
PUERTO RICO,		
Caguas – COMP REP ASSOC, INC	(787) 746-6550	
UTAH,		
Murray – FRONT RANGE MARKETING	(801) 288-2500	
WASHINGTON,		
Kirkland – ELECTRA TECHNICAL SALES	(206) 821-7442	
WISCONSIN,		
Pewaukee – Industrial Representatives, Inc.	(414) 574-9393	

Advanced Micro Devices reserves the right to make changes in its product without notice in order to improve design or performance characteristics. The performance characteristics listed in this document are guaranteed by specific tests, guard banding, design and other practices common to the industry. For specific testing details, contact your local AMD sales representative. The company assumes no responsibility for the use of any circuits described herein.





One AMD Place
P.O. Box 3453
Sunnyvale,
California 94088-3453
408-732-2400
800-538-8450
TWX 910-339-9280
TELEX 34-6306

**TECHNICAL SUPPORT &
LITERATURE ORDERING**

USA & Canada 800-222-9323
USA PC CPU Technical Support 408-749-3060
JAPAN 03-3346-7550
Fax 03-3346-9628
FAR EAST Fax 852-2956-0599
EUROPE & UK +44-(0)-1276-803299
Fax +44-(0)-1276-803298
BBS +44-(0)-1276-803211
FRANCE 0800-908621
GERMANY 089-450-53199
ITALY 1678-77224
ARGENTINA 001-800-200-1111,
after tone 888-263-8500
BRAZIL 000-811-718-5573
CHILE 800-570-048
MEXICO 95-800-263-4758

PC CPU Technical Support E-mail: hwsupt@brahms.amd.com
Europe Technical Support E-mail: euro.tech@amd.com
Europe Literature Request E-mail: euro.lit@amd.com
<http://www.amd.com>



RECYCLED &
RECYCLABLE

Printed in USA
Con-5.4M-3/97-0
20734D